



SPHERICAL ROLLER BEARINGS

Bore Diameter 60 – 90 mm




Cylindrical Bore



Tapered Bore



Without an Oil Groove or Holes

**Dynamic Equivalent Load**

$$P = XF_r + YF_a$$

$F_a/F_r \leq e$		$F_a/F_r > e$	
X	Y	X	Y
1	Y_3	0.67	Y_2

Static Equivalent Load

$$P_0 = F_r + Y_0 F_a$$

The values of e , Y_2 , Y_3 , and Y_0 are given in the table below.

Boundary Dimensions (mm)				Basic Load Ratings (N)		Speeds (min^{-1}) Limiting Speeds				Bearing Designations		Abutment and Fillet Dimensions (mm)					Constant	Axial Load Factors			Mass (kg)
d	D	B	r min.	C_r	C_{0r}	Thermal Speed Rating (Oil Bath)	Mechanical (Forced Oil Circulation)	Grease	Oil (Oil Bath)	Cylindrical Bore	Tapered Bore ⁽¹⁾	d_a min.	d_a max.	D_a max.	D_a min.	r_a max.	e	Y_2	Y_3	Y_0	approx.
60	95	26	1.1	98 500	141 000	4 800	—	3 600	4 500	23012CE4	23012CKE4	67	68	88	85	1	0.26	3.9	2.6	2.5	0.68
	110	28	1.5	178 000	174 000	5 300	8 000	4 800	6 000	*22212EAE4	*22212EAKE4	69	72	101	98	1.5	0.23	4.4	3.0	2.9	1.1
	130	31	2.1	238 000	244 000	4 800	6 700	3 800	4 800	*21312EAE4	*21312EAKE4	72	87	118	117	2	0.22	4.5	3.0	3.0	1.98
	130	46	2.1	340 000	340 000	4 000	5 600	3 600	4 500	*22312EAE4	*22312EAKE4	72	79	118	111	2	0.34	3.0	2.0	1.9	2.89
65	120	31	1.5	221 000	230 000	4 800	7 500	4 300	5 300	*22213EAE4	*22213EAKE4	74	80	111	107	1.5	0.24	4.2	2.8	2.7	1.51
	140	33	2.1	264 000	275 000	4 500	6 000	3 600	4 500	*21313EAE4	*21313EAKE4	77	94	128	126	2	0.22	4.6	3.1	3.0	2.45
	140	48	2.1	375 000	380 000	3 800	5 000	3 200	4 000	*22313EAE4	*22313EAKE4	77	84	128	119	2	0.34	3.0	2.0	2.0	3.52
70	125	31	1.5	225 000	232 000	4 500	7 100	4 000	5 300	*22214EAE4	*22214EAKE4	79	84	116	111	1.5	0.23	4.3	2.9	2.8	1.58
	150	35	2.1	310 000	325 000	4 300	5 600	3 200	4 000	*21314EAE4	*21314EAKE4	82	101	138	135	2	0.22	4.6	3.1	3.0	3.0
	150	51	2.1	425 000	435 000	3 600	4 800	3 000	3 800	*22314EAE4	*22314EAKE4	82	91	138	129	2	0.33	3.0	2.0	2.0	4.28
75	130	31	1.5	238 000	244 000	4 300	6 700	4 000	5 000	*22215EAE4	*22215EAKE4	84	87	121	117	1.5	0.22	4.5	3.0	3.0	1.64
	160	37	2.1	310 000	325 000	4 000	5 600	3 200	4 000	*21315EAE4	*21315EAKE4	87	101	148	134	2	0.22	4.6	3.1	3.0	3.64
	160	55	2.1	485 000	505 000	3 400	4 300	2 800	3 600	*22315EAE4	*22315EAKE4	87	97	148	137	2	0.33	3.0	2.0	2.0	5.26
80	140	33	2	264 000	275 000	4 000	6 000	3 600	4 500	*22216EAE4	*22216EAKE4	90	94	130	126	2	0.22	4.6	3.1	3.0	2.01
	170	39	2.1	355 000	375 000	3 800	4 800	3 000	3 800	*21316EAE4	*21316EAKE4	92	109	158	146	2	0.23	4.4	3.0	2.9	4.32
	170	58	2.1	540 000	565 000	3 200	3 800	2 600	3 400	*22316EAE4	*22316EAKE4	92	103	158	145	2	0.33	3.0	2.0	2.0	6.23
85	150	36	2	310 000	325 000	4 000	5 600	3 400	4 300	*22217EAE4	*22217EAKE4	95	101	140	135	2	0.22	4.6	3.1	3.0	2.54
	180	41	3	360 000	395 000	3 800	5 000	3 000	4 000	*21317EAE4	*21317EAKE4	99	108	166	142	2.5	0.24	4.3	2.9	2.8	5.2
	180	60	3	600 000	630 000	3 000	3 400	2 400	3 200	*22317EAE4	*22317EAKE4	99	110	166	155	2.5	0.33	3.1	2.1	2.0	7.23
90	160	40	2	360 000	395 000	3 800	5 000	3 200	4 000	*22218EAE4	*22218EAKE4	100	108	150	142	2	0.24	4.3	2.9	2.8	3.3
	160	52.4	2	340 000	490 000	2 800	—	1 800	2 400	23218CE4	23218CKE4	100	105	150	138	2	0.32	3.2	2.1	2.1	4.51
	190	43	3	415 000	450 000	3 600	4 500	2 800	3 600	*21318EAE4	*21318EAKE4	104	115	176	152	2.5	0.24	4.3	2.9	2.8	6.1
	190	64	3	665 000	705 000	2 800	3 000	2 400	3 000	*22318EAE4	*22318EAKE4	104	115	176	163	2.5	0.33	3.1	2.1	2.0	8.56

Note ⁽¹⁾ Suffix K represents bearings with tapered bores (taper 1:12).

Remarks

- Bearings denoted by an asterisk (*) are NSKPS bearings; they come standard with an oil groove and holes.
- The recommended fits (shaft tolerances) on Page A164 are different for NSKPS bearings, with light loads defined as $\leq 0.05C_r$, normal loads as 0.05 to $0.10C_r$, and heavy loads as $> 0.10C_r$.
- For the dimensions of adapters and withdrawal sleeves, refer to Pages C349 – C350 and C356.